# LaGrangian Formulation of System Dynamics

### Find the dynamics of a nonlinear system:

Circuit analysis tools work for simple lumped systems. For more complex systems, especially nonlinear ones, this approach fails. The Lagrangian formulation for system dynamics is a way to deal with any system.

## Definitions:

- KE Kinetic Energy in the system
- PE Potential Energy
- $\frac{\partial}{\partial t}$  The partial derivative with respect to 't'. All other variables are treated as constants.
- $\frac{d}{dt}$  The full derivative with respect to t.

$$\frac{d}{dt} = \frac{\partial}{\partial x}\frac{\partial x}{\partial t} + \frac{\partial}{\partial y}\frac{\partial y}{\partial t} + \frac{\partial}{\partial z}\frac{\partial z}{\partial t} + \dots$$

L Lagrangian = KE - PE

### **Procedure:**

- 1) Define the kinetic and potential energy in the system.
- 2) Form the Lagrangian:

$$L = KE - PE$$

3) The input is then

$$\boldsymbol{F}_{i} = \frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\boldsymbol{x}}_{i}} \right) - \frac{\partial L}{\partial \boldsymbol{x}_{i}}$$

where  $F_i$  is the input to state  $x_i$ . Note that

- If  $x_i$  is a position,  $F_i$  is a force.
- If  $x_i$  is an angle,  $F_i$  is a torque

## Example:

Example: Determine the dynamics of a rocket

Step 1: Determine the potential and kinetic energy of the rocket

Potential Energy

Kinetic Energy:

$$KE = \frac{1}{2}m\dot{x}^2$$

Step 2: Set up the LaGrangian

$$L = KE - PE$$
$$L = \frac{1}{2}m\dot{x}^2 - mgx$$

Step 3: Take the partials

$$F = \frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\mathbf{x}}} \right) - \left( \frac{\partial L}{\partial \mathbf{x}} \right)$$
$$F = \frac{d}{dt} (m \dot{\mathbf{x}}) - (-mg)$$

Take the full derivative with respect to t

$$F = m\ddot{x} + \dot{m}\dot{x} + mg$$

Note that if the rocket is loosing mass you get the term  $\dot{m}\dot{x}$ . If you leave this term out, the rocket misses the target.

# Example 2: Ball in a parabolic bowl



Determine the dynamics of a ball rolling in a bowl characterized by

$$y = \frac{1}{2}x^2$$

Step 1: Define the kinetic and potential energy

Potential Energy:

$$PE = mgy = \frac{1}{2}mgx^2$$

Kinetic Energy: This has two terms, one for translation and one for rotation .

$$\mathbf{K}\mathbf{E} = \frac{1}{2}\mathbf{m}\mathbf{v}^2 + \frac{1}{2}\mathbf{J}\dot{\mathbf{\Theta}}^2$$

The velocity is

$$\mathbf{v} = \sqrt{\dot{\mathbf{x}}^2 + \dot{\mathbf{y}}^2}$$

The rotational velocity is

$$position = r\theta$$

$$\mathbf{v} = r\dot{\mathbf{\theta}}$$

Note that

 $y = \frac{1}{2}x^2$  $\dot{y} = x\dot{x}$ 

gives

$$KE = \frac{1}{2}mv^{2} + \frac{1}{2}J(\frac{v}{r})^{2}$$
$$KE = \frac{1}{2}\left(m + \frac{J}{r^{2}}\right)v^{2}$$
$$KE = \frac{1}{2}\left(m + \frac{J}{r^{2}}\right)(\dot{x}^{2} + \dot{y}^{2})$$
$$KE = \frac{1}{2}\left(m + \frac{J}{r^{2}}\right)\left(\dot{x}^{2} + (x\dot{x})^{2}\right)$$

The inertia depends upon what type of ball you are using:

$$J = 0$$
point mass with all the mass in the center $J = \frac{2}{5}mr^2$ solid sphere $J = \frac{2}{3}mr^2$ hollow sphere $J = mr^2$ hollow cyllinder

Assume the ball is a solid sphere

$$KE = \frac{1}{2} \left( m + \frac{\frac{2}{5}mr^2}{r^2} \right) \left( \dot{x}^2 + (x\dot{x})^2 \right)$$
$$KE = 0.7m(1^2 + x^2)\dot{x}^2$$

Step 2: Form the LaGrangian

$$L = KE - PE$$
  
L = 0.7m(1<sup>2</sup> + x<sup>2</sup>) $\dot{x}^2 - \frac{1}{2}mgx^2$ 

Step 3: Take the partials. The partial with respect to x is:

$$\frac{\partial L}{\partial x} = 0.7m(2x)\dot{x}^2 - mgx$$
$$\frac{\partial L}{\partial x} = 1.4mx\dot{x}^2 - mgx$$

The partial with respect to dx/dt is:

$$\frac{\partial L}{\partial \dot{x}} = 1.4m(1^2 + x^2)\dot{x}$$

/

The full derivative of the partial with respect to dx/dt is

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\mathbf{x}}} \right) = \frac{d}{dt} (1.4m(1^2 + \mathbf{x}^2)\dot{\mathbf{x}})$$
$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\mathbf{x}}} \right) = 1.4m(2\mathbf{x}\dot{\mathbf{x}})\dot{\mathbf{x}} + 1.4m(1^2 + \mathbf{x}^2)\ddot{\mathbf{x}}$$
$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\mathbf{x}}} \right) = 2.8m\mathbf{x}\dot{\mathbf{x}}^2 + 1.4m(1^2 + \mathbf{x}^2)\ddot{\mathbf{x}}$$

So, the dynamics are:

$$F = \frac{d}{dt} \left( \frac{\partial L}{\partial \dot{x}} \right) - \left( \frac{\partial L}{\partial x} \right)$$
  

$$F = (2.8mx\dot{x}^2 + 1.4m(1^2 + x^2)\ddot{x}) - (1.4mx\dot{x}^2 - mgx)$$
  

$$F = 1.4mx\dot{x}^2 + 1.4m(1^2 + x^2)\ddot{x} + mgx$$

In free fall, F = 0. Solving for the highest derrivative:

$$\ddot{\mathbf{X}} = -\left(\frac{\left(1.4\dot{\mathbf{x}}^2 + g\right)\mathbf{x}}{1.4\left(1^2 + \mathbf{x}^2\right)}\right)$$

#### NDSU

#### Matlab Code (Ball.m)

```
% Dynamics of a ball rolling in a bowl where
y = 1/2 x^2
9
x = 1.5;
dx = 0;
dt = 0.01;
t = 0;
while (t < 100)
% compute the acceleration
ddx = -(1.4*dx*dx + 9.8) * x / (1.4*(1 + x*x));
% integrate
dx = dx + ddx * dt;
x = x + dx * dt;
% display the ball
y = 0.5 * x * x;
x1 = [-2:0.01:2]';
 y1 = 0.5* (x1 .^{2});
 % draw the ball
 i = [0:0.01:1]' * 2 * pi;
 xb = 0.05 * cos(i) + x;
 yb = 0.05 + sin(i) + 0.5 + x^2 + 0.05 + 0.02 + abs(x);
 % line through the ball
 q = [0, pi] - x/0.05;
 xb1 = 0.05 * cos(q) + x;
 yb1 = 0.05*sin(q) + 0.5*x^2 + 0.05 + 0.02*abs(x);
 plot(x1,y1,'b', xb, yb, 'r', xb1, yb1, 'r');
 pause(0.01);
 end
```